




**BELMONT
MEDICAL
TECHNOLOGIES**

Saving Lives. Together.

CRITICOOL®

Safe, Precise, and Effective^{1,2}


PATIENT TEMPERATURE MANAGEMENT



TARGETED TEMPERATURE MANAGEMENT



INFANT



PEDIATRIC



ADULT

CRITICOOL®

CritiCool® is a thermal regulating system indicated for maintaining pre-set body temperature as determined by a physician. The system is composed of two elements, the CritiCool device and the CureWrap™.

The CritiCool device functions as a control unit for use with the CureWrap. The control unit reads the patient's core temperature through specific probes every 66 milliseconds and adjusts temperature as necessary in order to maintain the physician determined pre-set temperature settings.

The cooling/heating pump brings the water to the temperature set point and circulates it in a closed-loop system through the uniquely designed CureWrap.

FAST. SIMPLE. PRECISE.

- Accurate temperature control as set by the physician
- Full-color, touch-screen display
- Simple, easy to use interface with intuitive controls
- Real-time monitoring and graphical display of temperature measurements
- Quick and easy setup
- Track data using the CliniLogger™

CUREWRAP™



The CureWrap is a single use, one-piece flexible garment that acts in conjunction with the CritiCool control unit. The CureWrap's flexible configurations facilitate the wrapping of individual parts of the body to maximize surface coverage.

The CureWrap is designed to conveniently attach to the control unit using Quick Coupling Connectors (QCC) that allow for inflow and outflow. Integrated channels within the suit-like garment circulate water in a closed-loop system over a large surface area.

The CureWrap is secured via pressure sensitive adhesive strips which adhere to the garment, and not the patient.


DESIGNED WITH YOUR PATIENT IN MIND

- One-piece body shaped garment with various sizes and configurations
- Up to 85% body surface area coverage
- Soft mesh that is easy to wrap and secure
- Clutter-free with only one pair of connecting tubes



TARGETED TEMPERATURE MANAGEMENT HAS NEVER BEEN EASIER

- +** SET
Select the desired temperature set point
- 👉** WRAP
Apply the CureWrap garment
- ❄️** COOL
Initiate fast cooling
- 🔥** REWARM
Manage controlled rewarming



The CureWrap is available in a range of sizes and designs to accommodate your patient's anatomy:

WRAP TYPE	PACK TYPE	PART NUMBER	QUANTITY PER BOX	PATIENT HEIGHT/WEIGHT	WRAP LENGTH/WIDTH (M)
Infant	Single Size	508-03518	8	2.5-4 kg (5.5- 8.8 lb)	0.659 / 0.448
		508-03521	8	4-7 kg (8.8-15.4 lb)	0.698 / 0.602
Pediatric (Small)	Assorted Sizes	PED-SM008	8	(x4) 2.5-4 kg (5.5- 8.8 lb)	0.659 / 0.448
			(multi-size)	(x4) 4-7 kg (8.8-15.4 lb)	0.698 / 0.602
Pediatric (Medium)		PED-MD008	8	(x4) 7-11 kg (15.4-24.3 lb)	0.981 / 0.628
		(multi-size)	(x4) 79-91 cm (31-36")	1.118 / 0.740	
Pediatric (Large)	PED-LA008	8	(x4) 91-104 cm (36-41")	1.225 / 0.841	
	(multi-size)	(x4) 104-122 cm (41-48")	1.390 / 1.054		
Pediatric (X-Large)	PED-XL008	8	(x4) 122-135 cm (48-53")	1.582 / 1.193	
	(multi-size)	(x4) Over 135 cm (Over 53")	2.030 / 1.354		
Adult	Single Size	508-03500	8	Over 135 cm (Over 53") Fits most adults	2.030 / 1.354

1 Stafford et al.: Therapeutic Hypothermia During Neonatal Transport: Active Cooling Helps Reach the Target. THERAPEUTIC HYPOTHERMIA AND TEMPERATURE MANAGEMENT 2016.
2 Glover et al.: Intravascular versus surface cooling for targeted temperature management after out-of-hospital cardiac arrest – an analysis of the TTM trial data. Critical Care 2016 20:381.

ORDERING INFORMATION

CONTROL UNIT

CritiCool® (115V)	Part #100-00003
CritiCool® (230V)	Part #100-00004
CritiCool® (100V)	Part #100-00007

CRITICOOL ACCESSORY KIT (Select one only for each CritiCool unit)

INFANT KIT FOR DISPOSABLE TEMPERATURE SENSORS **Part #200-00330**

The Infant Kit contains:

- Core Adapter Cable Part #014-00028
- Surface Adapter Cable Part #014-00129
- Connecting Water Tubes (2 by 2 way) Part #200-00109

ADULT KIT FOR DISPOSABLE TEMPERATURE SENSORS **Part #200-00310**

The Adult Kit contains:

- Core Adapter Cable Part #014-00028
- Surface Adapter Cable Part #014-00129
- Connecting Water Tubes (2 by 3 way) Part #200-00147

Note: Disposable Temperature Probes must be ordered separately.

REUSABLE KITS:

(NOT AVAILABLE IN THE UNITED STATES AND SELECT MARKETS)

INFANT REUSABLE KIT **Part #200-00320**

The Infant Kit contains:

- Reusable Core Temperature Probe, Infant Part #014-00005
- Reusable Surface Temperature Probe Part #014-00021
- Filter unit Part #200-R0130
- Connecting Water Tubes (2 by 2 way) Part #200-00109

ADULT REUSABLE KIT **Part #200-00300**

The Adult Kit contains:

- Reusable Core Temperature Probe, Adult Part #014-00020
- Reusable Surface Temperature Probe Part #014-00021
- Filter unit Part #200-R0130
- Connecting Water Tubes (2 by 3 way) Part #200-00147

ACCESSORIES

Disposable Core Temperature Probe	Part #014-00322
Disposable Surface Temperature Probe	Part #014-00321
CliniLogger™	Part #017-00250

Note: Connecting Water Tubes (2 by 3 way) (Part #200-00147) is required for Pediatric X-Large CureWrap (Part #PED-XL008) and for Adult CureWrap (Part #508-03500).

HARDWARE SPECIFICATIONS

HEAT EXCHANGERS

Peltier Technology (TECs)

WATER TANK

Sterile or 0.22 micron filtered tap water
Tank Capacity: 6 liters (1.6 gal.)

WATER TEMPERATURE

Water Temperature Accuracy: $\pm 0.3^{\circ}\text{C}$ (0.54°F)
Water Temperature (outflow): $13\text{--}40.8^{\circ}\text{C}$ ($55.4\text{--}105.4^{\circ}\text{F}$)

PUMP

Water Circulating Pump
Pump Rate: 1.2 L/min
Protected by 263 micron filter

PATIENT TEMPERATURE CHANNELS

2 Channels: Core, Surface
Sensor Temperature Range: 15°C to 44°C (59°F to 111.2°F)
Sensor Temperature Accuracy: $\pm 0.3^{\circ}\text{C}$ (0.45°F)

TEMPERATURE AND PRESSURE SENSORS

System Sensors:

- 3 Internal Temperature Sensors: Water in, Water out, Thermostat
- 2 Pressure sensors

Safety Measures:

- Over pressure protection and alarm
- High water temperature protection and alarm

PHYSICAL DIMENSIONS

Mobile unit with 4 wheels and 2 brakes
260 mm W x 625 mm D x 940 mm H /
(10.23"W x 24.6"D x 37"H)

NET WEIGHT

34 kg / 75 lb

INPUT POWER

115VAC 5.7 A 50/60 HZ
230VAC 2.9 A 50/60 HZ
100VAC 6.6 A 50/60 HZ

LCD DISPLAY

Size: 5.7" color display
Resolution: 320x240

CUREWRAP™

Single Patient Use

For more information about the products we offer,
contact us at sales@belmontmedtech.com.



PATIENT
WARMING



PATIENT
COOLING



FLUID
MANAGEMENT



780 BOSTON ROAD
BILLERICA, MA 01821, USA
USA: 866.663.0212
WORLDWIDE: +1 978.663.0212
FAX: 978.663.0214
WWW.BELMONTMEDTECH.COM

